

TRAVEL $90^\circ \pm 5^\circ$ AT BOTH ENDS
RATIO 183:1
TURNS TO CLOSE 45.75
MECHANICAL ADVANTAGE ... $57 \pm 10\%$

MAXIMUM OUTPUT TORQUE (1000 CYCLES)..... 8000 Nm
MAXIMUM OUTPUT TORQUE (5000 CYCLES)..... 6600 Nm
MAXIMUM INPUT TORQUE (1000 CYCLES)..... 140 Nm
MAXIMUM INPUT TORQUE (5000 CYCLES)..... 115 Nm

MOUNTING HOLE DETAIL (BSENISO 5211:2001)


APPROXIMATE WEIGHT 46 kg

PREFERRED F25 (8 x M16 on 254 PCD)
MAXIMUM F25 (8 x M16 on 254 PCD)
MINIMUM F16 (4 x M20 on 165 PCD)



OPPERMAN MASTERGEAR

Hambridge Lane, Newbury, Berkshire, RG14 5TS. ENGLAND
Tel: 01635 811500 Fax: 01635 811501 E-Mail: sales@opperman-mastergear.co.uk



DIMENSIONS
IN
MM [INCHES]

DATE	09Jun05
DRAWN	PAB
CHECKED	KDR
SCALE	1:5