

OUTPUT KEYWAY DETAILS SHOWN IN OPEN POSITION

TRAVEL 90° ±5° AT BOTH ENDS
 RATIO 615:1
 TURNS TO CLOSE 153.75
 MECHANICAL ADVANTAGE ... 188.7 ±10%

MAXIMUM OUTPUT TORQUE (1000 CYCLES)..... 24000 Nm
 MAXIMUM OUTPUT TORQUE (2500 CYCLES)..... 20000 Nm
 MAXIMUM INPUT TORQUE (1000 CYCLES)..... 127 Nm
 MAXIMUM INPUT TORQUE (2500 CYCLES)..... 106 Nm


MOUNTING HOLE DETAIL (BSENISO 5211:2001)
 PREFERRED F40 (8 x M36 on 406 PCD)
 MAXIMUM F40 (8 x M36 on 406 PCD)
 MINIMUM F25 (8 x M16 on 254 PCD)

APPROXIMATE WEIGHT 181.5 kg



OPPERMAN MASTERGEAR

Hambridge Lane, Newbury, Berkshire, RG14 5TS. ENGLAND
 Tel: 01635 811500 Fax: 01635 811501 E-Mail: sales@opperman-mastergear.co.uk



DIMENSIONS IN
 MM [INCHES]

DATE	24Apr06
DRAWN	TK
CHECKED	BJH
SCALE	1:7

This drawing/design is the property of OPPERMAN MASTERGEAR Ltd. © and must not be used or copied without their specific written consent. Specifications may change without prior notification

DRG No. ME-15440

REV. A